



Fourth Committee Draft (4CD)

Project: Revision of OIML R 129:2000

Title: Multi-dimensional Measuring Instruments
Part 3 – Test report format

Date: 20 December 2019

Document number: TC7_SC5_P1_N044 (clean)

Supersedes document: TC7_SC5_P1_N027

Project Group: TC 7/SC 5/p 1

Convenership: Australia and Canada

INTERNATIONAL **OIML R 129-3**
RECOMMENDATION Edition 202x (E)

Multi-dimensional Measuring Instruments
Part 3: Test report format

Instruments de mesure multidimensionnels

Partie 3: Format du rapport d'essais



Contents

[BIML Note: Clause numbers and references (in brackets) to R 129-1 and R 129-2 will be updated in the next version]

Foreword	5
Introduction	6
Test report	7
Explanatory notes	7
Identification of the instrument	9
General information concerning the type	12
Information concerning the test equipment used for type evaluation	15
Configuration for test	16
Adjustments or modifications.....	17
Summary of type evaluation tests.....	18
2.2 Instrument warm up time (A.1.1)	19
2.3 Repeatability (A.1.2)	20
2.4 Static temperatures (A.2.1).....	21
2.4.1 Initial Reference temperature (A.2.1)	21
2.4.2 High and low temperatures	22
2.4.3 Reference temperature (A.2.1).....	23
2.5 Damp heat (A.2.2)	24
2.5.1 Steady state (non-condensing)	24
2.5.1.1 Initial reference temperature and 50% relative humidity (A.2.2.1)	24
2.5.1.2 High temperature and 85% relative humidity (A.2.2.1)	25
2.5.1.3 End reference temperature and 50% relative humidity (A.2.2.1)	26
2.5.2 Cyclic (condensing)	27
2.5.2.1 Damp heat cyclic (A.2.2.2).....	27
2.6 AC mains voltage variation (A.2.3).....	28
2.6.1 Nominal Voltage (A.2.3)	28
2.6.2 Nominal Voltage -15% (A.2.3).....	29
2.6.3 Nominal Voltage +10% (A.2.3).....	30
2.7 Low voltage of internal battery (A.2.4).....	31
2.7.1 Nominal Voltage (A.2.4)	31
2.7.2 Low Voltage (A.2.4)	32
2.8 AC mains voltage dips, short interruptions and reductions (A.3.1).....	33
2.9 Electrical bursts (A.3.2).....	34
2.9.1 Power supply lines (A.3.2).....	34
2.9.2 Input / Output circuits and communication lines (A.3.2).....	35
2.10 Electrostatic discharge (A.3.3)	36
2.10.1 Direct Application (A.3.3)	36
2.10.2 Indirect Application (A.3.3).....	37
2.10.3 Electrostatic discharge additional sheet (A.3.3).....	38
2.11 Electrical surges (A.3.4).....	39
2.11.1 Surges on AC mains.....	39
2.11.1.1 Surges on AC mains power lines (A.3.4.1)	39
2.11.1.2 AC surge voltage at 0° (A.3.4.1)	40
2.11.1.3 AC surge voltage at 90° (A.3.4.1)	41
2.11.1.4 AC surge voltage at 180° (A.3.4.1)	42
2.11.1.5 AC surge voltage at 270° (A.3.4.1)	43
2.11.2 Surges on signal, data and control lines (A.3.4.2).....	44
2.12 Immunity to RF Electromagnetic fields (A.3.5).....	45
2.12.1 Radiated RF electromagnetic fields (A.3.5.1).....	45
2.12.2 Conducted RF electromagnetic fields (A.3.5.2)	46
2.12.3 Additional Sheet	47
2.13 Ambient light (A.4.1)	48

2.13.1 Reference conditions 200 lx to 500 lx (A.4.1)	48
2.13.2 Ambient light 100 lx (A.4.1).....	49
2.13.3 Ambient light 1000 lx to 1500 lx (A.4.1).....	50
2.13.4 Ambient light unknown lx (A.4.1).....	51
2.13.5 Additional sheet (A.4.1).....	52
2.14 Acoustics (A.4.2).....	53
2.14.1 Reference sound level (dB) (A.4.2)	53
2.14.2 100 dB sound level (dB) (A.4.2).....	54
2.14.3 Additional Sheet	55
2.15 Shape of the object (A.1.7).....	56
2.16 Uniform surface colour (A.1.7)	57
2.17 Non uniform surface colour (A.1.7)	58
2.18 Contrast of colour with background colour (A.1.7).....	59
2.19 Surface reflectivity and absorption of sound (A.1.7).....	60
2.20 Surface reflectivity and absorption of light (A.1.7).....	61
2.21 Uniformity of density (A.1.7).....	62
2.22 Transparency (A.1.7).....	63
2.23 Surface roughness (A.1.7)	64
2.24 Protrusions on surface (A.1.7).....	65
2.25 Orientation and position (A.1.7).....	66
2.26 Test for speed of relative movement (A.1.7).....	67
2.26.1 Minimum speed (A.1.7).....	67
2.26.2 Maximum speed (A.1.7)	68
2.27 Examination of the construction of instrument (R 126-1, clause 5.1.2)	69

Foreword

The International Organization of Legal Metrology (OIML) is a worldwide, intergovernmental organization whose primary aim is to harmonize the regulations and metrological controls applied by the national metrological services, or related organizations, of its Member States. The main categories of OIML publications are:

- § **International Recommendations (OIML R)**, which are model regulations that establish the metrological characteristics required of certain measuring instruments and which specify methods and equipment for checking their conformity. OIML Member States shall implement these Recommendations to the greatest possible extent;
- § **International Documents (OIML D)**, which are informative in nature and which are intended to harmonize and improve work in the field of legal metrology;
- § **International Guides (OIML G)**, which are also informative in nature and which are intended to give guidelines for the application of certain requirements to legal metrology; and
- § **International Basic Publications (OIML B)**, which define the operating rules of the various OIML structures and systems.

OIML Draft Recommendations, Documents and Guides are developed by Project Groups linked to Technical Committees or Subcommittees which comprise representatives from the Member States. Certain international and regional institutions also participate on a consultation basis. Cooperative agreements have been established between the OIML and certain institutions, such as ISO and the IEC, with the objective of avoiding contradictory requirements. Consequently, manufacturers and users of measuring instruments, test laboratories, etc. may simultaneously apply OIML publications and those of other institutions.

International Recommendations, Documents, Guides and Basic Publications are published in English (E) and translated into French (F) and are subject to periodic revision.

Additionally, the OIML publishes or participates in the publication of **Vocabularies (OIML V)** and periodically commissions legal metrology experts to write **Expert Reports (OIML E)**. Expert Reports are intended to provide information and advice, and are written solely from the viewpoint of their author, without the involvement of a Technical Committee or Subcommittee, nor that of the CIML. Thus, they do not necessarily represent the views of the OIML.

This publication - reference OIML R 129-3, Edition 202x - was developed by Project Group 1 of OIML TC 7/SC 5 *Dimensional Measuring Instruments*. It was approved for final publication by the International Committee of Legal Metrology in 202x and will be submitted to the International Conference of Legal Metrology in 202x for formal sanction.

OIML Publications may be downloaded from the OIML web site in the form of PDF files. Additional information on OIML Publications may be obtained from the Organization's headquarters:

Bureau International de Métrologie Légale
11, rue Turgot - 75009 Paris - France
Telephone: 33 (0)1 48 78 12 82
Fax: 33 (0)1 42 82 17 27
E-mail: biml@oiml.org
Internet: www.oiml.org

Introduction

The “Test report format”, the subject of OIML R 129-3, aims at presenting, in a standardized format, the results of the various tests and examinations to which a type of a multi-dimensional measuring instrument shall be submitted with a view to its approval.

The “Test report” is a record of the results of the tests carried out on the instrument. The “test report” forms have been produced based on the tests detailed in the performance test procedures (OIML R 129-2).

The “information concerning the test equipment used for type evaluation” shall cover all test equipment which has been used in determining the test results given in a report. The information may be a short list containing essential data (name, type, reference number for purpose of traceability). For example:

- § Verification standards (accuracy or accuracy class, and no.);
- § Simulator for testing of modules (name, type, traceability and no.);
- § Climatic test and static temperature chamber (name, type and no.);
- § Electrical tests, bursts (name of the instrument, type and no.);
- § Description of the procedure of field calibration for the electromagnetic susceptibility test.

All metrology services or laboratories evaluating types of multi-dimensional measuring instrument according to OIML R 129-1 and -2 or to national or regional regulations based on OIML R 129-1 and -2 are strongly advised to use this “Test report format”, directly or after translation into a language other than English or French. Its direct use in English or in French, or in both languages, is even more strongly recommended whenever test results may be transmitted by the country performing these tests to the approving authorities of another country, under bi- or multi-lateral cooperation agreements. In the framework of the OIML Certification System (OIML-CS), use of the “Test report format” is mandatory.

Test report

Explanatory notes

Meaning of symbols used in this report

L	= Indicated length
W	= Indicated width
H	= Indicated height
L_T	= Length of the test object
DL	= Error, $L - L_T$
W_T	= Width of the test object
DW	= Error, $W - W_T$
H_T	= Height of the test object
DH	= Error, $H - H_T$
MPE	= Maximum permissible error
V	= The volume indicated on the instrument
V _{calc}	= $L \times W \times H$
F	= Conversion factor
DW	= The dimensional weight indicated on the instrument
DW _{calc}	= $V \times F$
SF	= Significant fault

Explanatory notes (continued)

The name(s) or symbol(s) of the unit(s) used to express test results shall be specified on each form.

The boxes under the headings of the report should always be filled in according to the following example:

	At start	At end	
Temp.:	20.5	21.1	°C
Rel. h.:			%
Date:	2014-10-15	2014-10-15	yyyy-mm-dd
Time:	16:00:05	16:30:05	hh:mm:ss

where: Temp. = temperature
Rel. h. = relative humidity

“Date” in the test report refers to the date on which the test was performed.

“ID” refers to the identity of the test object used (e.g. unique identifying number) and is entered in the appropriate columns as required.

Identification of the instrument

Application no.:	Type designation:
Identification no.:	Manufacturer:
Software version:		
Report date:		

Documentation from the manufacturer

(Record as necessary to identify the equipment under test)

System or module name	Drawing number or software reference	Issue level	Serial no.
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....

Simulator documentation (if applicable)

System or module name	Drawing number or software reference	Issue level	Serial no.
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....

Identification of the instrument (continued)

Application no.:	Type designation:
Identification no.:	Manufacturer:
Software version:		
Report date:		

Simulator function (summary) (if applicable)

(Simulator description and drawings, block diagram, etc. should be attached to the report if available)

Identification of the instrument (continued)

Application no.:	Type designation:
Identification no.:	Manufacturer:
Software version:		
Report date:		

Physical description of the instrument

Describe, using point form, the physical construction of the MDMI (materials, configuration and location of components, interfaces and communications ports). Attach photographs, diagrams or drawings if available:

Describe, using point form, the measurement technology used (include details such as physical contact method; laser class, power and wavelength; ultrasonic frequency; or camera spectrum):

General information concerning the type

Application no.: Manufacturer:
 Type designation: Applicant:
 Instrument category:

Parameter limits		
	Minimum	Maximum
Temperature limits (°C)		
Speed limitations (m/s)		
Voltage (V)		
Minimum spacing		/

Limitation	Check if applicable
Object	
Cuboidal	
Irregular	
Singulated	
Non-singulated, non-touching	
Touching	
Measurement dynamics	
Static measurement only	
Fixed Speed	
Variable Speed	
Unidirectional	
Bidirectional	
Installation	
Permanent	
Mobile	
Power Supply	
AC	
AC-DC converter	
Battery	
DC	

Evaluation period:
 Date of report:
 Observer:

General information concerning the type (continued)

Application no.: Manufacturer:

Type designation: Applicant:

Instrument category:

Scale Interval and limits of indication

Axis	Unit of measurement	Scale interval (d)	Minimum dimension	Maximum dimension
X				
Y				
Z				

Describe, using point form, each axis and its relation to the physical object being measured and/or the MDMI itself:

Use this space to describe, using point form, any other use or installation limitations not detailed in the above on the previous page (such as special applications other than postage, freight or storage; restrictions on object material, texture, reflectivity or colour; object positioning):

Use this space to indicate additional remarks and/or information: connecting equipment, interfaces, choice of the manufacturer regarding protection against disturbances, etc.

General information concerning the type (continued)

Application no.: Manufacturer:

Type designation: Applicant:

Instrument category:

Indications and controls

Describe, using point form, all indications and controls of the instrument (such as wired or wireless communication with instrument; zero method; ready indication, computed quantities, error codes). Describe each measurement (L, W, and H) and its relation to the physical object being measured and/or the MDMI itself:

Sealing

Describe, using point form, the physical and electronic seals (e.g. audit trails) used to protect the metrological characteristics of the instrument, and how to access them. Also describe any remote access abilities available and how this is sealed:

Software

Describe, using point form, the means used to protect legally relevant software in the instrument and indicate the version of the software present at the time of testing and how to verify this version number:

Information concerning the test equipment used for testing

Application no.: Type designation:

Report date: Manufacturer:

List all test equipment used in this report (including descriptions of the equipment used for testing)

Equipment name	Manufacturer	Type no.	Serial no.	Used for (test references)
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....
.....

Configuration for test

Application no.: Type designation:
 Report date: Manufacturer:

Use this space for additional information relating to equipment configuration, interfaces, data rates, EMC protection options etc., for the instrument and/or simulator.

Calibration information

Calibration principle

Calibration number	GT1	GT2	etc*
Version number:			
Displayed name:			
Date submitted:			

Regression information -

Approx number of data points:			
Data sources, date range			
Reference method(s):			
Other validation result (e.g. SD, SEP)			
Default slope (if applic):			
Default bias (if applic):			
Other characteristic:			

*Copy table into additional pages if more than two calibrations are submitted for examination

Comments:

Adjustments or modifications

Application no.: Type designation:
Report date: Manufacturer:

Use this space for additional information relating to the identification of any authorized and agreed upon adjustments or modifications made to the sample or samples during the evaluation.

Summary of type evaluation tests

Application no.: Type designation:
 Report date: Manufacturer:

2. Type Evaluation Tests

2.1. SUMMARY OF TYPE EVALUATION

Report No.:
 Application No.:
 Manufacturer:
 Make & Model:

Section	Test	Report Page	Pass	Fail	Remarks
2.2	Instrument warm up time (A.1.1)				
2.3	Repeatability (A.1.2)				
2.4	Static temperatures (A.2.1)				
2.4.1	Initial reference temperature = °C				
2.4.2	High temperature = °C				
2.4.3	Low temperature = °C				
2.4.3	End reference temperature= °C				
2.5	Damp heat (A.2.2)				
2.5.1	Steady State (non-condensing) (A.2.2.1)				
2.5.1.1	Initial reference temperature and 50% relative humidity				
2.5.1.2	High temperature and 85% relative humidity				
2.5.1.3	End reference temperature and 50% relative humidity				
2.5.2	Cyclic (condensing) (A.2.2.2)				
2.5.2.1	DH cyclic				
2.6	AC mains voltage variation (A.2.3)				
2.6.1	Nominal voltage				
2.6.2	Nominal voltage + 10%				
2.6.3	Nominal voltage - 15%				
2.7	Low voltage of internal battery (A.2.4)				
2.7.1	Nominal voltage				
2.7.2	Low voltage				
2.8	AC mains voltage dips, short interruptions and reductions (A.3.1)				
2.9	Electrical bursts test (A.3.2)				
2.9.1	Power supply lines				
2.9.2	Input/output control circuits and communication lines				
2.10	Electrostatic discharge (A.3.3)				
2.10.1	Direct application				
2.10.2	Indirect application				
2.10.3	Additional Sheet				
2.11	Electrical surges (A.3.4)				
2.11.1	Surges on AC mains power lines (A.3.4.1)				
2.11.1.1	Surges on AC mains power lines				
2.11.1.2	AC surge voltage at 0°				
2.11.1.3	AC surge voltage at 90°				
2.11.1.4	AC surge voltage at 180°				
2.11.1.5	AC surge voltage at 270°				
2.11.2	Surges on signal, data and control lines (A.3.4.2)				
2.12	Immunity to RF Electromagnetic fields (A.3.5)				
2.12.1	Radiated RF electromagnetic fields (A.3.5.1)				
2.12.2	Conducted RF electromagnetic fields (A.3.5.2)				
2.12.3	Additional Sheet				
2.13	Ambient light (A.4.1)				
2.13.1	200 lx to 500 lx (reference)				
2.13.2	100 lx				
2.13.3	1000 lx to 1500 lx				
2.13.4	Unknown intensity lx				
2.13.5	Additional Sheet				
2.14	Acoustics (A.4.2)				
2.14.1	Reference sound level (dB)				
2.14.2	Sound Level 100 dB				
2.14.3	Additional Sheet				
2.15	Shape of the object (A.1.7)				
2.16	Uniform surface colour test (A.1.7)				
2.17	Non uniform surface colour test (A.1.7)				
2.18	Contrast of colour with background colour test (A.1.7)				
2.19	Surface reflectivity and absorption of sound test (A.1.7)				
2.20	Surface reflectivity and absorption of colour test (A.1.7)				
2.21	Uniformity of density test (A.1.7)				
2.22	Transparency test (A.1.7)				
2.23	Surface roughness test (A.1.7)				
2.24	Protrusions on the surface test (A.1.7)				
2.25	Orientation and position test (A.1.7)				
2.26	Speed of relative movement test (A.1.7)				
2.26.1	Minimum speed				
2.26.2	Maximum speed				
2.27	Examination of the construction of the instrument (R129-1, clause 5.1.2)				
OVERALL RESULT					

2.2 Instrument warm up time (A.1.1)

Observer:
 Type/ application #:
 Instrument 1 ID:
 Instrument 2 ID:

General comments on test:

Ambient temp (t):
 Ambient RH:
 Date commenced:
 Time commenced:

Not warm	Warm	
		°C
		%
		ddmmyyyy
		hh:mm

Instrument 1, close to minimum dimensions	Instrument ID <input style="width: 40px;" type="text"/>
Length = <input style="width: 100px;" type="text"/> unit= <input style="width: 100px;" type="text"/>	Width = <input style="width: 100px;" type="text"/> unit= <input style="width: 100px;" type="text"/>
	Height = <input style="width: 100px;" type="text"/> unit= <input style="width: 100px;" type="text"/>

Instrument 2, close to maximum dimensions	Instrument ID <input style="width: 40px;" type="text"/>
Length = <input style="width: 100px;" type="text"/> unit= <input style="width: 100px;" type="text"/>	Width = <input style="width: 100px;" type="text"/> unit= <input style="width: 100px;" type="text"/>
	Height = <input style="width: 100px;" type="text"/> unit= <input style="width: 100px;" type="text"/>

Instrument 1 (close to minimum dimensions)		Instrument ID <input style="width: 40px;" type="text"/>							
Time (units)	Initial zeroing/Ready state (Yes/No)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
0 minutes									
5 minutes									
15 minutes									
30 minutes									

Instrument 2 (close to maximum dimensions)		Instrument ID <input style="width: 40px;" type="text"/>							
Time (units)	Initial zeroing/Ready state (Yes/No)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
0 minutes									
5 minutes									
15 minutes									
30 minutes									

Remarks

RESULT : PASS FAIL

2.3 Repeatability (A.1.2)

Observer: _____
 Type/ application #: _____
 Instrument ID: _____
 Scale Interval (d): _____
 Conversion Factor (F) _____

Temp (°C) At start At end
 RH (%) _____
 Time _____
 Date _____

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = _____ unit= _____	Width = _____ unit= _____	Height = _____ unit= _____	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no
----------------	----------------------------	---------------------------	----------------------------	-----------------------------------	---

Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1												
2												
3												

Test object ID	Length = _____ unit= _____	Width = _____ unit= _____	Height = _____ unit= _____	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no
----------------	----------------------------	---------------------------	----------------------------	-----------------------------------	---

Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1												
2												
3												

Test object ID	Length = _____ unit= _____	Width = _____ unit= _____	Height = _____ unit= _____	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no
----------------	----------------------------	---------------------------	----------------------------	-----------------------------------	---

Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1												
2												
3												

Test object ID	Length = _____ unit= _____	Width = _____ unit= _____	Height = _____ unit= _____	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no
----------------	----------------------------	---------------------------	----------------------------	-----------------------------------	---

Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1												
2												
3												

Test object ID	Length = _____ unit= _____	Width = _____ unit= _____	Height = _____ unit= _____	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no
----------------	----------------------------	---------------------------	----------------------------	-----------------------------------	---

Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1												
2												
3												

Remarks

RESULT: PASS FAIL

2.4 Static temperatures (A.2.1)

2.4.1 Initial Reference temperature (A.2.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.4 Static temperatures (A.2.1)

2.4.2 High and low temperatures

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	High temperature		Pass/Fail
												Dwcalc		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Low temperature		Pass/Fail
												Dwcalc		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.4 Static temperatures (A.2.1)

2.4.3 Reference temperature (A.2.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: **PASS** **FAIL**

2.5 Damp heat (A.2.2)

2.5.1 Steady state (non-condensing)

2.5.1.1 Initial reference temperature and 50% relative humidity (A.2.2.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: **PASS** **FAIL**

2.5 Damp heat (A.2.2)

2.5.1 Steady state (non-condensing)

2.5.1.2 High temperature and 85% relative humidity (A.2.2.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: **PASS** **FAIL**

2.5 Damp heat (A.2.2)

2.5.1 Steady state (non-condensing)

2.5.1.3 End reference temperature and 50% relative humidity (A.2.2.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected
 but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT:

PASS

FAIL

2.5 Damp heat (A.2.2)

2.5.2 Cyclic (condensing)

2.5.2.1 Damp heat cyclic (A.2.2.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	Indication			SF > d	SF*	Result	Comment	Ref Temp (°C)
		L	W	H					<input type="text"/>
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	Y/N	Y/N	PASS/FAIL	<input type="text"/>	
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	

Damp heat, cyclic (24 h x 2 cycles)

Test Object ID	Initial zeroing (yes/no)	Indication			SF > d	SF*	Result	Comment	Ref Temp (°C)
		L	W	H					<input type="text"/>
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	Y/N	Y/N	PASS/FAIL	<input type="text"/>	
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	

1. SF* - Significant Fault detected and acted upon.

Remarks

RESULT: PASS FAIL

2.6 AC mains voltage variation (A.2.3)

2.6.1 Nominal Voltage (A.2.3)

Observer: []
 Type/ application #: []
 Instrument ID: []
 Scale Interval (d): []
 Conversion Factor (F) []

	At start	At end
Temp (°C)	[]	[]
RH (%)	[]	[]
Nominal Voltage (V)	[]	[]
Time	[]	[]
Date	[]	[]

Auxiliary Device : Connected [] Not connected but connectable [] Not connected []

Correct indication of Auxiliary device [] (yes/no)

Conveyor Speed (m/min): minimum [] maximum [] other []

Test Object ID	Length (units)	Width (units)	Height (units)
1	[]	[]	[]
2	[]	[]	[]
3	[]	[]	[]
4	[]	[]	[]
5	[]	[]	[]

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
2	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
3	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
4	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]
5	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]	[]

Remarks

RESULT: **PASS** [] **FAIL** []

2.6 AC mains voltage variation (A.2.3)

2.6.2 Nominal Voltage -15% (A.2.3)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Nominal Voltage + 10% (V)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.6 AC mains voltage variation (A.2.3)

2.6.3 Nominal Voltage +10% (A.2.3)

Observer:

Type/ application #:

Instrument ID:

Scale Interval (d):

Conversion Factor (F)

Temp (°C)

RH (%)

Nominal Voltage - 15% (V)

Time

Date

At start	At end
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.7 Low voltage of internal battery (A.2.4)

2.7.1 Nominal Voltage (A.2.4)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	Temp (°C)	At start	At end
	RH (%)	<input type="text"/>	<input type="text"/>
Marked Nominal Voltage (V)		<input type="text"/>	<input type="text"/>
Time		<input type="text"/>	<input type="text"/>
Date		<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.7 Low voltage of internal battery (A.2.4)

2.7.2 Low Voltage (A.2.4)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Low Voltage (V)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial zeroing (yes/no)	L	ΔL	W	ΔW	H	ΔH	MPE	V	Vcalc	DW	Dwcalc	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: **PASS** **FAIL**

2.8 AC mains voltage dips, short interruptions and reductions (A.3.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected
 but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID <input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>
-------------------------------------	---	--	---	--------------------------------------	----------------------

Instrument

Reduction in amplitude (as % marked nom voltage)	Duration (in cycles) units	Number of disturbances	Time between disturbances	Indication			SF > d Y/N	SF* Y/N	Result PASS/FAIL	Comment
				L	W	H				
0	0	0	-							
100	0.5	10	10 s							
0	0	0	-							
50	0.5	10	10 s							

Auxillary Device

Reduction in amplitude (as % marked nom voltage)	Duration (in cycles) units	Number of disturbances	Time between disturbances	Indication			SF > d Y/N	SF* Y/N	Result PASS/FAIL	Comment
				L	W	H				
0	0	0	-							
100	0.5	10	10 s							
0	0	0	-							
50	0.5	10	10 s							

- 1. SF* - Significant Fault detected and acted upon.
- 2. amplitude* - In case of a marked voltage range, use the average value as the marked nominal voltage.

Remarks

RESULT: PASS FAIL

2.9 Electrical bursts (A.3.2)

2.9.1 Power supply lines (A.3.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected Not connected but connectable

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID <input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition) <input type="checkbox"/>	yes <input type="checkbox"/> no <input type="checkbox"/>
-------------------------------------	--	---	--	--	---

Instrument

	Connection			Polarity	Results						
	L	N	PE		L	Indication		H	SF > d	SF *	Result
	ground	ground	ground			W		Y/N	Y/N	PASS/FAIL	
Without disturbance X				pos neg							
Without disturbance		X		pos neg							
Without disturbance			X	pos neg							

NOTES: 1. SF * - Significant fault detected and acted upon.
 2. L = Phase, N = Neutral , PE = Protective Earth

Auxiliary device

	Connection			Polarity	Results						
	L	N	PE		L	Indication		H	SF > d	SF *	Result
	ground	ground	ground			W		Y/N	Y/N	PASS/FAIL	
Without disturbance X				pos neg							
Without disturbance		X		pos neg							
Without disturbance			X	pos neg							

NOTES: 1. SF * - Significant fault detected and acted upon.
 2. L = Phase, N = Neutral , PE = Protective Earth

Remarks

RESULT: **PASS** **FAIL**

2.9 Electrical bursts (A.3.2)

2.9.2 Input / Output circuits and communication lines (A.3.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected Not connected but connectable

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>
		Initial zeroing (Ready condition)	<input type="checkbox"/>	yes	<input type="checkbox"/>	no	<input type="checkbox"/>

Connection	Polarity	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
Without disturbance	pos	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	neg	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Without disturbance	pos	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	neg	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Without disturbance	pos	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	neg	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Without disturbance	pos	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	neg	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Without disturbance	pos	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
	neg	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

NOTES: 1. SF * - Significant fault detected and acted upon.

Remarks:
 (Explain or make a sketch indicating the loaction of clamp on the cable.)

RESULT: **PASS** **FAIL**

2.10 Electrostatic discharge (A.3.3)

2.10.1 Direct Application (A.3.3)

Observer:
Type/ application #:
Instrument ID:
Scale Interval (d):
Conversion Factor (F)

Table with 2 columns: At start, At end. Rows for Temp (°C), RH (%), Time, Nominal Voltage (V), Date.

Auxiliary Device: Connected, Not connected but connectable, Not connected
Correct indication of Auxiliary device (yes/no)
Conveyor Speed (m/min): minimum, maximum, other
Contact discharges, Air discharges, Paint penetration
Polarity ** positive, negative

Test object ID, Length, Width, Height, Initial zeroing (Ready condition), yes/no

Instrument table with columns: Test Voltage (kV), Disturbance (No. of discharges, Rep. interval), Indication (L, W, H), Results (SF > d, SF *, Result, Comment)

Note: SF * - Significant fault detected and acted upon.

Auxiliary device table with columns: Test Voltage (kV), Disturbance (No. of discharges, Rep. interval), Indication (L, W, H), Results (SF > d, SF *, Result, Comment)

Note: SF * - Significant fault detected and acted upon.

Remarks: [Large empty box for notes]

NOTES:
1. 8* - Air discharges
2. If the EUT fails, record the test point at which the EUT fails.
3. Polarity ** - Tests shall be conducted at the most sensitive polarity.

RESULT: PASS FAIL

2.10 Electrostatic discharge (A.3.3)

2.10.2 Indirect Application (A.3.3)

Observer: []
 Type/ application #: []
 Instrument ID: []
 Scale Interval (d): []
 Conversion Factor (F): []

Temp (°C)	At start	At end
RH (%)	[]	[]
Time	[]	[]
Date	[]	[]

Nominal Voltage (V) []

Auxiliary Device : Connected [] Not connected []
 Not connected but connectable [] Not connected []

Correct indication of Auxiliary device [] (yes/no)

Conveyor Speed (m/min): minimum [] maximum [] other []
 Contact discharges [] Air discharges [] Paint penetration []
 Polarity ** [] positive [] negative []

Test object ID	Length = [] unit= []	Width = [] unit= []	Height = [] unit= []	Initial zeroing (Ready condition)	Yes [] No []
----------------	---------------------------	--------------------------	---------------------------	--------------------------------------	-------------------------

Horizontal coupling plane

Disturbance			Results						
Test Voltage (kV)	No. of discharges	Rep. interval (s)	L	W	H	SF > d	SF *	Result	Comment
units									
Without disturbance									
2	[]	[]	[]	[]	[]	[]	[]	[]	[]
4	[]	[]	[]	[]	[]	[]	[]	[]	[]
6	[]	[]	[]	[]	[]	[]	[]	[]	[]
8*	[]	[]	[]	[]	[]	[]	[]	[]	[]

Note SF * - Significant fault detected and acted upon.

Vertical coupling plane

Disturbance			Results						
Test Voltage (kV)	No. of discharges	Rep. interval (s)	L	W	H	SF > d	SF *	Result	Comment
units									
Without disturbance									
2	[]	[]	[]	[]	[]	[]	[]	[]	[]
4	[]	[]	[]	[]	[]	[]	[]	[]	[]
6	[]	[]	[]	[]	[]	[]	[]	[]	[]
8*	[]	[]	[]	[]	[]	[]	[]	[]	[]

Note SF * - Significant fault detected and acted upon.

Remarks:

[]

- NOTES:**
- 1. 8* - Air discharges
 - 2. If the EUT fails, recored the test point at which the EUT fails.
 - 3. Polarity ** - Tests shall be conducted at the most sensitive polarity.

RESULT: PASS [] FAIL []


2.10 Electrostatic discharge (A.3.3)

2.10.3 Electrostatic discharge additional sheet (A.3.3)


Specifications of test points of EUT (eg) photos or sketches

a) Direct application

Contact discharges:




Air discharges:




b) Indirect application

Contact discharges:



Air discharges:



2.11 Electrical surges (A.3.4)

2.11.1 Surges on AC mains

2.11.1.1 Surges on AC mains power lines (A.3.4.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected
 Correct indication of Auxiliary device (yes/no)
 Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/> yes <input type="text"/> no
----------------	--	---	--	-----------------------------------	---

DC Mains Power Instrument

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

Note: 1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Auxiliary Devices

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

Note: 1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Remarks:

RESULT: PASS FAIL

2.11 Electrical surges (A.3.4)

2.11.1 Surges on AC mains

2.11.1.2 AC surge voltage at 0° (A.3.4.1)

Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = <input type="text"/>	Width = <input type="text"/>	Height = <input type="text"/>	Initial zeroing (Ready condition)	yes
	unit= <input type="text"/>	unit= <input type="text"/>	unit= <input type="text"/>		no

AC surge voltage at 0°

Instrument

Connection	Mode	Results						Comment
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Auxiliary Devices

Connection	Mode	Results						Comment
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Remarks:

RESULT: PASS FAIL

2.11 Electrical surges (A.3.4)

2.11.1 Surges on AC mains

2.11.1.3 AC surge voltage at 90° (A.3.4.1)

Observer: []
 Type/ application #: []
 Instrument ID: []
 Scale Interval (d): []
 Conversion Factor (F) []

	At start	At end
Temp (°C)	[]	[]
RH (%)	[]	[]
Time	[]	[]
Nominal Voltage (V)	[]	[]
Date	[]	[]

Auxiliary Device : Connected [] Not connected [] Not connected but connectable []

Correct indication of Auxiliary device [] (yes/no)

Conveyor Speed (m/min): minimum [] maximum [] other []

Test object ID	Length = [] unit= []	Width = [] unit= []	Height = [] unit= []	Initial zeroing (Ready condition)	yes [] no []
----------------	---------------------------	--------------------------	---------------------------	--------------------------------------	-------------------

AC surge voltage at 90°

Instrument

Connection	Mode	Results						
		L	W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)		[]	[]	[]	[]	[]	[]	[]
Positive	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
Negative	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
Positive	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]
Negative	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Auxiliary Devices

Connection	Mode	Results						
		L	W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)		[]	[]	[]	[]	[]	[]	[]
Positive	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
Negative	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
	L-L	[]	[]	[]	[]	[]	[]	[]
Positive	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]
Negative	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]
	L-E	[]	[]	[]	[]	[]	[]	[]

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Remarks:

RESULT: **PASS** []

FAIL []

2.11 Electrical surges (A.3.4)

2.11.1 Surges on AC mains

2.11.1.4 AC surge voltage at 180° (A.3.4.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = <input type="text"/>	Width = <input type="text"/>	Height = <input type="text"/>	Initial zeroing (Ready condition)	yes
	unit= <input type="text"/>	unit= <input type="text"/>	unit= <input type="text"/>		no

AC surge voltage at 180°

Instrument

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Auxillary Devices

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Remarks:

RESULT: PASS FAIL

2.11 Electrical surges (A.3.4)

2.11.1 Surges on AC mains

2.11.1.5 AC surge voltage at 270° (A.3.4.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected Not connected
 but connectable

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	yes no
----------------	---	--	---	--------------------------------------	-----------

AC surge voltage at 270°

Instrument

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Auxiliary Devices

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Remarks:

RESULT: PASS FAIL

2.11 Electrical surges (A.3.4)

2.11.2 Surges on signal, data and control lines (A.3.4.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	yes no
----------------	---	--	---	-----------------------------------	-----------

Connection	Mode	Results						
		L	Indication W	H	SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
No Surge (reference condition)								
Positive	L-L							
	L-L							
	L-L							
Negative	L-L							
	L-L							
	L-L							
Positive	L-E							
	L-E							
	L-E							
Negative	L-E							
	L-E							
	L-E							

1. SF * - Significant fault detected and acted upon.
 2. L-L - Line to Line Surge
 3. L-E - Line to Earth Surge

Remarks:

RESULT: PASS FAIL

2.12 Immunity to RF Electromagnetic fields (A.3.5)

2.12.1 Radiated RF electromagnetic fields (A.3.5.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Rate of sweep:

Test object ID	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	yes <input type="text"/> no <input type="text"/>
----------------	--	---	--	-----------------------------------	---

Disturbance				Results						
Antenna	Frequency range	Antenna polarisation	Facing EUT	Indication			SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
				L	W	H				
Without disturbance										
		Vertical	Front							
			Right							
			Left							
			Rear							
Without disturbance										
		Horizontal	Front							
			Right							
			Left							
			Rear							

NOTES: 1. SF * - Significant fault detected and acted upon.

Frequency range : 26 MHz to 2000 MHz
 Field strength: 10 V/m
 Modulation 80 % Am, 1 KHz sine wave

Remarks:

RESULT: **PASS** **FAIL**

2.12 Immunity to RF Electromagnetic fields (A.3.5)

2.12.2 Conducted RF electromagnetic fields (A.3.5.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Nominal Voltage (V)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Rate of sweep:

Test object ID	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	yes <input type="checkbox"/> no <input type="checkbox"/>
----------------	--	---	--	-----------------------------------	---

Disturbance				Results						
Antenna	Frequency range	Antenna polarisation	Facing EUT	Indication			SF > d Y/N	SF * Y/N	Result PASS/FAIL	Comment
				L	W	H				
Without disturbance										
		Vertical	Front							
			Right							
			Left							
			Rear							
Without disturbance										
		Horizontal	Front							
			Right							
			Left							
			Rear							

NOTES: 1. SF * - Significant fault detected and acted upon.

Frequency range : 0.15 MHz to 80 MHz
 Field strength: 10 V/m
 Modulation 80 % Am, 1 KHz sine wave


Remarks:

RESULT: **PASS** **FAIL**

2.12 Immunity to RF Electromagnetic fields (A.3.5)

2.12.3 Additional Sheet

1. Description of the set up of the EUT, eg. by photos ,sketches etc.

A large, empty rectangular box with a thin black border, intended for providing a description of the EUT setup, including photos or sketches.

2. Additional Remarks

A large, empty rectangular box with a thin black border, intended for providing additional remarks.

2.13 Ambient light (A.4.1)

2.13.1 Reference conditions 200 lx to 500 lx (A.4.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Light (lx)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial Zeroing (yes/no)	L (units)	ΔL	W (units)	ΔW	H (units)	ΔH	MPE	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>

Remarks

RESULT: **PASS** **FAIL**

2.13 Ambient light (A.4.1)

2.13.2 Ambient light 100 lx (A.4.1)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Light (lx)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial Zeroing (yes/no)	L (units)	ΔL	W (units)	ΔW	H (units)	ΔH	MPE	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="checkbox"/>

Remarks

RESULT: **PASS** **FAIL**

2.13 Ambient light (A.4.1)

2.13.3 Ambient light 1000 lx to 1500 lx (A.4.1)

Observer:	<input type="text"/>					At start	At end
Type/ application #:	<input type="text"/>					<input type="text"/>	<input type="text"/>
Instrument ID:	<input type="text"/>				Temp (°C)	<input type="text"/>	<input type="text"/>
Scale Interval (d):	<input type="text"/>				RH (%)	<input type="text"/>	<input type="text"/>
Conversion Factor (F)	<input type="text"/>				Time	<input type="text"/>	<input type="text"/>
					Light (lx)	<input type="text"/>	<input type="text"/>
					Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1			
2			
3			
4			
5			

Test Object ID	Initial Zeroing (yes/no)	L (units)	ΔL	W (units)	ΔW	H (units)	ΔH	MPE	Pass/Fail
1									
2									
3									
4									
5									

Remarks

RESULT: **PASS** **FAIL**

2.13 Ambient light (A.4.1)

2.13.4 Ambient light unknown lx (A.4.1)

Observer:

Type/ application #:

Instrument ID:

Scale Interval (d):

Conversion Factor (F):

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Light (lx)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial Zeroing (yes/no)	L (units)	ΔL	W (units)	ΔW	H (units)	ΔH	MPE	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>


Remarks

RESULT: **PASS** **FAIL**


2.13 Ambient light (A.4.1)

2.13.5 Additional sheet (A.4.1)

1. Description of the set up of the EUT, eg. photos or sketches

A large, empty rectangular box with a thin black border, intended for providing a description of the set up of the EUT, such as photos or sketches.

2. Additional remarks

A large, empty rectangular box with a thin black border, intended for providing additional remarks.

2.14 Acoustics (A.4.2)

2.14.1 Reference sound level (dB) (A.4.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Sound (dB)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial Zeroing (yes/no)	L (units)	ΔL	W (units)	ΔW	H (units)	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: **PASS** **FAIL**

2.14 Acoustics (A.4.2)

2.14.2 100 dB sound level (dB) (A.4.2)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F)

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Sound (dB)	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxillary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test Object ID	Length (units)	Width (units)	Height (units)
1	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test Object ID	Initial Zeroing (yes/no)	L (units)	ΔL	W (units)	ΔW	H (units)	ΔH	MPE	Pass/Fail
1	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
4	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
5	<input type="checkbox"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>


Remarks

RESULT: **PASS** **FAIL**


2.14 Acoustic Test (A.4.2)

2.14.3 Additional Sheet

1. Description of the set up of the EUT, eg. photos or sketches



2. Additional remarks



2.15 Shape of the object (A.1.7)

Observer:

Type/ application #:

Instrument ID:

Scale Interval (d):

Conversion Factor (F):

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>		

Remarks

RESULT: PASS FAIL

2.16 Uniform surface colour (A.1.7)

Observer:	<input type="text"/>	At start	At end
Type/ application #:	<input type="text"/>	Temp (°C)	<input type="text"/>
Instrument ID:	<input type="text"/>	RH (%)	<input type="text"/>
Scale Interval (d):	<input type="text"/>	Time	<input type="text"/>
Conversion Factor (F)	<input type="text"/>	Date	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Remarks

RESULT: PASS FAIL

2.17 Non uniform surface colour (A.1.7)

Observer:

Type/ application #:

Instrument ID:

Scale Interval (d):

Conversion Factor (F):

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.18 Contrast of colour with background colour (A.1.7)

Observer:

Type/ application #:

Instrument ID:

Scale Interval (d):

Conversion Factor (F):

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			

Test object ID	<input type="text"/>	Length = <input type="text"/>	unit= <input type="text"/>	Width = <input type="text"/>	unit= <input type="text"/>	Height = <input type="text"/>	unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>			

Remarks

RESULT: PASS FAIL

2.19 Surface reflectivity and absorption of sound (A.1.7)

Observer:		At start	At end
Type/ application #:		Temp (°C)	
Instrument ID:		RH (%)	
Scale Interval (d):		Time	
Conversion Factor (F)		Date	

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Remarks

RESULT: PASS FAIL

2.20 Surface reflectivity and absorption of light (A.1.7)

Observer:

Type/ application #:

Instrument ID:

Scale Interval (d):

Conversion Factor (F):

Temp (°C) At start At end

RH (%)

Time

Date

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/> yes <input type="checkbox"/> no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Remarks

RESULT: PASS FAIL

2.21 Uniformity of density (A.1.7)

Observer:	<input type="text"/>	Temp (°C)	At start	At end
Type/ application #:	<input type="text"/>	RH (%)	<input type="text"/>	<input type="text"/>
Instrument ID:	<input type="text"/>	Time	<input type="text"/>	<input type="text"/>
Scale Interval (d):	<input type="text"/>	Date	<input type="text"/>	<input type="text"/>
Conversion Factor (F)	<input type="text"/>			

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Remarks

RESULT: PASS FAIL

2.22 Transparency (A.1.7)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F):

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxillary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	Length = unit=	Width = unit=	Height = unit=	Initial zeroing (Ready condition)	yes	no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	Length = unit=	Width = unit=	Height = unit=	Initial zeroing (Ready condition)	yes	no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	Length = unit=	Width = unit=	Height = unit=	Initial zeroing (Ready condition)	yes	no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	Length = unit=	Width = unit=	Height = unit=	Initial zeroing (Ready condition)	yes	no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Test object ID	Length = unit=	Width = unit=	Height = unit=	Initial zeroing (Ready condition)	yes	no		
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1								
2								
3								

Remarks

RESULT: PASS FAIL

2.23 Surface roughness (A.1.7)

Observer:	<input type="text"/>	At start	At end
Type/ application #:	<input type="text"/>	Temp (°C)	<input type="text"/>
Instrument ID:	<input type="text"/>	RH (%)	<input type="text"/>
Scale Interval (d):	<input type="text"/>	Time	<input type="text"/>
Conversion Factor (F)	<input type="text"/>	Date	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Remarks

RESULT: PASS FAIL

2.24 Protrusions on surface (A.1.7)

Observer:
 Type/ application #:
 Instrument ID:
 Scale Interval (d):
 Conversion Factor (F):

	At start	At end
Temp (°C)	<input type="text"/>	<input type="text"/>
RH (%)	<input type="text"/>	<input type="text"/>
Time	<input type="text"/>	<input type="text"/>
Date	<input type="text"/>	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no	
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no	
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no	
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no	
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Test object ID	<input type="text"/>	Length = <input type="text"/> unit= <input type="text"/>	Width = <input type="text"/> unit= <input type="text"/>	Height = <input type="text"/> unit= <input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no	
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail
1	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
2	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
3	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

Remarks

RESULT: PASS FAIL

2.25 Orientation and position (A.1.7)

Observer:	<input type="text"/>	At start	At end
Type/ application #:	<input type="text"/>	Temp (°C)	<input type="text"/>
Instrument ID:	<input type="text"/>	RH (%)	<input type="text"/>
Scale Interval (d):	<input type="text"/>	Time	<input type="text"/>
Conversion Factor (F)	<input type="text"/>	Date	<input type="text"/>

Auxiliary Device : Connected Not connected but connectable Not connected

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="text"/>	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Remarks

RESULT: PASS FAIL

2.26 Test for speed of relative movement (A.1.7)

2.26.1 Minimum speed (A.1.7)

Observer:	<input type="text"/>	At start	At end
Type/ application #:	<input type="text"/>	Temp (°C)	<input type="text"/>
Instrument ID:	<input type="text"/>	RH (%)	<input type="text"/>
Scale Interval (d):	<input type="text"/>	Time	<input type="text"/>
Conversion Factor (F):	<input type="text"/>	Date	<input type="text"/>

Auxiliary Device : Connected Not connected Not connected but connectable

Correct indication of Auxiliary device (yes/no)

Conveyor Speed (m/min): minimum maximum other

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Test object ID	<input type="text"/>	Length = unit=	<input type="text"/>	Width = unit=	<input type="text"/>	Height = unit=	<input type="text"/>	Initial zeroing (Ready condition)	<input type="checkbox"/>	yes <input type="checkbox"/>	no <input type="checkbox"/>
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail			
1											
2											
3											

Remarks

RESULT: PASS FAIL

2.26 Test for speed of relative movement (A.1.7)

2.26.2 Maximum speed (A.1.7)

Observer: _____
 Type/ application #: _____
 Instrument ID: _____
 Scale Interval (d): _____
 Conversion Factor (F) _____

	At start	At end
Temp (°C)		
RH (%)		
Time		
Date		

Auxiliary Device : Connected _____ Not connected _____ Not connected _____
 but connectable

Correct indication of Auxiliary device _____ (yes/no)

Conveyor Speed (m/min): minimum _____ maximum _____ other _____

Test object ID	_____	Length = unit=	_____	Width = unit=	_____	Height = unit=	_____	Initial zeroing Ready condition)	_____	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	_____	Length = unit=	_____	Width = unit=	_____	Height = unit=	_____	Initial zeroing Ready condition)	_____	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	_____	Length = unit=	_____	Width = unit=	_____	Height = unit=	_____	Initial zeroing Ready condition)	_____	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	_____	Length = unit=	_____	Width = unit=	_____	Height = unit=	_____	Initial zeroing Ready condition)	_____	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										

Test object ID	_____	Length = unit=	_____	Width = unit=	_____	Height = unit=	_____	Initial zeroing Ready condition)	_____	yes no
Run (units)	L	ΔL	W	ΔW	H	ΔH	MPE	Pass/Fail		
1										
2										
3										


Remarks

RESULT: PASS _____ FAIL _____

2.27 Examination of the construction of instrument (R 126-1, clause 5.1.2)

Use this page to indicate any description or information pertaining to the instrument, additional to that already contained in this report and in the accompanying certificate of approval or OIML certificate of conformity.

This may include a pictures of the complete instrument, a description of its main components and any remark which could be useful for initial or subsequent verifications of individual instruments built according to the pattern. It may also include references to the manufacturer's description.

**RESULT:****PASS****FAIL**